

Gokin

470-500W



Higher Generated Energy



Higher Reliability



Lower BOS



Excellent Micro-crack Resistance



High Temperature Restriction



Partial Shading Optimisation



Extraordinary Aesthetic Design

24.5%

≤

First-year Degradation

≤

Annual Degradation



Product Warranty



Linear Power Warranty



CE

• Operating Temperature

-40°C ~ +85°C

• Power Tolerance

0~+3%

• Junction Box

IP68

• NOCT


• Maximum Series Fuse Rating

30A

• Maximum System Voltage

1500V(IEC)

Cell Type	GBC
No. of cells	
Glass	Dual glass, 2.0 + 2.0mm coated semi tempered glass
Frame	Black anodized aluminum
Output Cables	, (+)300mm, (-)200mm or Customized Length
Dimension	
Connector	
Packaging	
Protection Class	
Fire Rating	



Module Type														
Testing Condition	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT	STC	NOCT
	38.80													
	32.0131.1132.2032.30													
	12.0312.2112.32													

Guaranteed Module Performance



-
-
-
- Front Side Maximum Static Loading
- Rear Side Maximum Static Loading
- Hailstone Test